

article#	9545311
article description	Distribution box rubber mobile Zirl BV 125/5 2x63/5 2x32/5 2x16/5 4x16 IP54
description long	<p>solid rubber distribution box series ZIRL IP54 527x400x270 (HxWxD) universal mit 2x carrying handle on top and 2x standing feet on the bottom (stackable) 2m cable H07RN-F 5G35mm² black with plug 125A 5p 400V 1xCEE-socket 125A 5p 400V protected with pre-fuse of supply line 2xCEE-socket 63A 5p 400V IP67 fused with 2xMCB 63A 3p C (MCB before RCFD) 2xCEE-socket 32A 5p 400V fused with 2xMCB 32A 3p C 2xCEE-socket 16A 5p 400V fused with 2xMCB 16A 3p C 4xCEE-socket 16A 3p 230V fused with 2xMCB 16A 1p C 4xSchuko-socket 16A250V IP54 fused with 2xLS 16A 1p C 2xRCD 63A/4/0.03A (TYPE A 63AT) over 2x CEE 63/5 1xRCD 63A/4/0.03A (TYP A 63AT) over 2x CEE 32/5 fused with 1xMCB 63A 3p C 1xRCD 63A/4/0.03A (TYP A 63AT) over all 16 outlets>1xMCB 63A 3p C MCB and RCD made by Eaton ÖVE / VDE distribution box is ready wired for using Note: Number of outgoing circuits (ready for operation) max. current limited by Ina!</p>
GTIN (EAN)	9003399521553
country of origin	AT
customs number	85371098
net weight	40.000 kg
minimum order quantity	1

ETIM 9.0	EC000379
CEE socket outlet 16 A	2x16A5p400V
CEE socket outlet 32 A	2x32A5p400V
CEE socket outlet 63 A	2x63A5p400V
CEE socket outlet 125 A	1x125A5p400V
Number of socket outlets with protective contact CEE 7/3 (type F)	4
Other fixtures and/or empty locations	4
Protection	Overcurrent switch
Leakage current type	A
Earth leakage switch	Earth leakage switch with IFN 30 mA (standard)
Number of miniature circuit breakers	10
Material housing	Rubber
Contact material	CuZn
Surface treatment contacts	Nickel-plated
Power supply/connection possibility	Feeder cable with plug
Number of poles mains connection	5
Type of mains connection	CEE 125 A
Cable length	5 m
Handling	Portable
Degree of protection (IP)	IP54
Colour	Black
Height	527 mm
Width	400 mm
Depth	270 mm







<https://www.pcelectric.at/shop/en/?func=detail&artnr=9545311>