OVE Austrian Electrotechnical Association

Eschenbachgasse 9 | 1010 Wien | Austria

ZVR: 327279890 | www.ove.at

OVE Certification

Kahlenberger Str. 2A | 1190 Wien | Austria T +43 1 370 58 06 | certification@ove.at

Validity of ÖVE-Certificates can be checked at www.ove.at



Page 1 of 4

ÖVE-CERTIFICATE

including the entitlement to use the Austrian Safety Mark



Certificate No.: 43-171-11 Valid from: 2023 04 19

until: 2025 04 19

The Austrian Electrotechnical Association (OVE) hereby grants the right to the company mentioned below to label the listed products with the Austrian Safety Mark.

PC Electric Ges.m.b.H. Company:

Diesseits 145

4973 St. Martin im Innkreis

Austria

Product: Plug for industrial purposes with switch or integral overcurrent protection

The products submitted by the applicant were type tested in accordance with the requirements of the technical standards and specifications listed in this certificate. OVE certifies the conformity of the listed products and those products manufactured strictly identical to the submitted ones (EN ISO/IEC 17067, Conformity Assessment Scheme Type 5).

The manufacturing process and the products are subject to ongoing surveillance based on harmonized European procedures. This certificate has been issued under the presumption and conditional on the fact that the applicant holds all necessary legal rights with regard to the product, presented for the testing and certification.

Results of testing are shown in file No(s).: TGM-VA EE 36086

Österreichischer Verband für Elektrotechnik

Head of OVE Certification

Digitally signed by I. Neumayer Email=t neumayer@ove.at


Digitally signed by T. Neumayer

Dipl.-Ing. T. Neumayer



Wien, 2023 03 06









Certificate No.: 43-171-11 Date: 2023 03 06

Page 2 of 4

Manufacturer:

PC Electric Ges.m.b.H. Diesseits 145 4973 St. Martin im Innkreis Austria

Factory location(s):

PC Electric Ges.m.b.H. Diesseits 145 4973 St. Martin im Innkreis Austria

Tested and certified according to:

ÖVE/ÖNORM EN 60309-1:2013-03-01 ÖVE/ÖNORM EN 60309-2:2013-03-01

This certificate is the basis for the EU Declaration of Conformity and the CE Marking by the manufacturer or his agent and shows the conformity of the certified product(s) with the listed standards as defined by the **EU Low-Voltage Directive 2014/35/EU**. For the presumption of conformity according to Art. 12 with the safety objectives according to Art. 3 of the Directive, transitional periods given in the Official Journal of the European Union have to be observed.

Product: Plug for industrial purposes with switch or integral overcurrent protection

Type designation: Trademark: Rating:

Serien 53... PCE / ELCEE

Rated operating voltage: 50-690 V Insulation voltage: AC 450/500/690 V IP 44 or IP 44/IP 54

see typecode





Certificate No.: 43-171-11

Date: 2023 03 06 Page 3 of 4

Typecode

53 clock position 2 3 2h 3h 4 4h 5 5h blank 6h 7 7h 9 9h 10 10h 11 11h 12h 12 operation display / rotation field check blank without operation display 1 3 rotation field check switch / setting range ON/OFF ML0 530 610 reversing switch K&N CA10 625 reversing switch K&N CA25 001 MS 0,10-0,16A 002 MS 0,16-0,25A 004 MS 0,25-0,40A 006 MS 0,40-0,63A 010 MS 0,63-1,0A 016 MS 1,0-1,6A 025 MS 1,6-2,5A 040 MS 2,5-4,0A 063 MS 4,0-6,3A 100 MS 6,3-10A 160 MS 10-16A 200 MS 16-20A 250 MS 20-25A 320 MS 25-32A MS 25-40A 400 **Poles** 4 4pole 5 5pole rated current 16A 2 32A plug / phase inverter 0 Plug Phase inverter ground type 53 rotary switch with holder

OVE Certification





Certificate No.: 43-171-11

Date: 2023 03 06 Page 4 of 4

Typelist

Туре	Poles	Rated current [A]	Clock position [h]	Rated operating voltage V IVI	Frequency [Hz]
53	4	16 or 32	1	Other ratings	Other ratings
			2*	> 50	> 300 – 500
			3	380, 440	50, 60
			4	100 – 130	50 and 60
			5	600 – 690	50 and 60
			6	380 – 415	50 and 60
			7	480 – 500	50 and 60
			9	200 – 250	50 and 60
			10*	> 50	> 100 – 300
			11	440 – 460	60
			12	Supply from an isolating transformer	50 and 60
53	5	16 or 32	1	Other ratings	Other ratings
			2*	> 50	> 300 – 500
			3	220/380, 250/440	50, 60
			4	57/100 – 75/130	50 and 60
			5	347/600 – 400/690	50 and 60
			6	200/346 – 240/415	50 and 60
			7	277/480 – 288/500	50 and 60
			9	200/208 - 144/250	50 and 60
			10*	> 50	100 – 300
			11	250/440 – 265/460	60
			12	Supply from an isolating transformer	50 and 60

^{*}only with switch PKZM0

