OVE Austrian Electrotechnical Association Eschenbachgasse 9 | 1010 Wien | Austria ZVR: 327279890 | www.ove.at

OVE Certification Kahlenberger Str. 2A | 1190 Wien | Austria T +43 1 370 58 06 | certification@ove.at

Validity of ÖVE-Certificates can be checked at www.ove.at



Page 1 of 6



including the entitlement to use the Austrian Safety Mark



Certificate No.: 43-176-10

Valid from: 2023 02 01 until: 2025 02 01

The Austrian Electrotechnical Association (OVE) hereby grants the right to the company mentioned below to label the listed products with the Austrian Safety Mark.

Company: PC Electric Ges.m.b.H. Diesseits 145 4973 St. Martin im Innkreis Austria

Product: Switched socket-outlets for fixed mounting

The products submitted by the applicant were type tested in accordance with the requirements of the technical standards and specifications listed in this certificate. OVE certifies the conformity of the listed products and those products manufactured strictly identical to the submitted ones (EN ISO/IEC 17067, Conformity Assessment Scheme Type 5).

The manufacturing process and the products are subject to ongoing surveillance based on harmonized European procedures. This certificate has been issued under the presumption and conditional on the fact that the applicant holds all necessary legal rights with regard to the product, presented for the testing and certification.

Results of testing are shown in file No(s).: TGM-VA EE 35769

Österreichischer Verband für Elektrotechnik Head of OVE Certification



T. Neumayer Digitally signed by T. Neumayer Email=t neumayer@ove.at Dipl.-Ing. T. Neumayer

Wien, 2023 02 09

OVE Certification



Accredited by the Federal Ministry for Digital and Economic Affairs as Certification Body for products within the scope as given in the official decree and published under https://akkreditierung-austria.gv.at.





Manufacturer:

PC Electric Ges.m.b.H. Diesseits 145 4973 St. Martin im Innkreis Austria

Factory location(s):

PC Electric Ges.m.b.H. Diesseits 145 4973 St. Martin im Innkreis Austria

PCE Polska Sp.z.o.o. ul Podwalna 8A 58-200 Dzierzoniow Poland

Tested and certified according to:

ÖVE/ÖNORM EN 60309-1:2013-03-01 ÖVE/ÖNORM EN 60309-2:2013-03-01 ÖVE/ÖNORM EN 60309-4:2012-12-01

This certificate is the basis for the EU Declaration of Conformity and the CE Marking by the manufacturer or his agent and shows the conformity of the certified product(s) with the listed standards as defined by the **EU Low-Voltage Directive 2014/35/EU**. For the presumption of conformity according to Art. 12 with the safety objectives according to Art. 3 of the Directive, transitional periods given in the Official Journal of the European Union have to be observed.

Product: Switched socket-outlets for fixed mounting

Type designation: Rating:	Trademark:	
960623 Rated current: 32 A Rated insulation voltage: 690 V IP44 or IP44/IP54 with switch, alternatively additional with maximal 2 socket outlet of Type 1050, 105 or 109	PCE / ELCEE	
960624 Rated current: 32 A Rated insulation voltage: 690 V IP44 or IP44/IP54 with switch, alternatively additional with maximal 2 socket outlet of Type 1050, 105 or 109	PCE / ELCEE	
		reditierung Au

Certificate No.: 43-176-10

Date: 2023 02 09

Page 2 of 6

OVE Certification



0	VE
	Austrian Electrotechnical Association

Certificate No.: 43-176-10 Date: 2023 02 09 Page 3 of 6

960625 Rated current: 32 A Rated insulation voltage: 690 V IP44 or IP44/IP54 with switch, alternatively additional with maximal 2 socket outlet of Type 1050, 105 or 109	PCE / ELCEE
960723 Rated current: 32 A Rated insulation voltage: 690 V IP67 or IP66/IP67 with switch, alternatively additional with maximal 2 socket outlet of Type 20351, 20352, 30351 or 30352	PCE / ELCEE
960724 Rated current: 32 A Rated insulation voltage: 690 V IP67 or IP66/IP67 with switch, alternatively additional with maximal 2 socket outlet of Type 20351, 20352, 30351 or 30352	PCE / ELCEE
960725 Rated current: 32 A Rated insulation voltage: 690 V IP67 or IP66/IP67 with switch, alternatively additional with maximal 2 socket outlet of Type 20351, 20352, 30351 or 30352	PCE / ELCEE

OVE Certification




Typecode

960 • 2 • • Special design blank....standard design *.....reserved for additonal versions (shutter, colour, etc.) **Clock position earthing contact** -1.....1h -3.....3h -44h -5.....5h blank....6h -77h -9.....9h -11.....11h -1212h Switch blank....ON/OFF Switch 1reversing switch Number of socket-outlet for household blank without socket-outlet for household 1one socket-outlet for household 2two socket-outlet for household optionally socket outlet for household 50without socket-outlet for household 5socket-outlet for household type 1050 (IP44), 20351-8* (IP67)reserved for additonal versions Poles 3socket-outlet type 423 (IP44), 4232 (IP67) 4socket-outlet type 424 (IP44), 4242 (IP67) 5socket-outlet type 425 (IP44), 4252 (IP67) **Rated current** 232A **Degree of protection** 6IP44 or IP44/IP54 7IP67 or IP66/IP67 Ground type 960switched socket-outlet

OVE Certification








Typelist

Туре	Poles	Clock position earthing contact [h]	Rated operating voltage V [V]	Frequency [Hz]	Degree of protection [IP]
960623		1	Other ratings	Other ratings	
		4	100 – 130	50 und 60	
	3	6*	200 – 250	50 und 60	-
		7	480 - 500	50 und 60	
		9*	380 – 415	50 und 60	
		12	Supply from an isolating transformer	50 und 60	
		1	Other ratings	Other ratings	
	4	3	380 440	50 60	
		4	100 – 130	50 und 60	IP44 or IP44/IP54
		5	600 - 690	50 und 60	
960624		6*	380 – 415	50 und 60	
		7	480 - 500	50 und 60	
		9*	200 – 250	50 und 60	
		11	440 - 460	60	
		12	Supply from an isolating transformer	50 und 60	
		1	Other ratings	Other ratings	
960625		3	220/380 250/440	50 60	
		4	57/100 - 75/130	50 und 60	
	5 5	5	347/600 - 400/690	50 und 60	
		6*	200/346 - 240/415	50 und 60	
		7	277/480 - 288/500	50 und 60	
		9*	120/208 - 144/250	50 und 60	
		11	250/440 - 265/460	60	
		12	Supply from an isolating transformer	50 und 60	

* Types with max 2 x socket outlet for household only available for clock position 6h or 9h.







Туре	Poles	Clock position earthing contact [h]	Rated operating voltage V [V]	Frequency [Hz]	Degree of protection [IP]
		1	Other ratings	Other ratings	
		4	100 – 130	50 und 60	
	3	6*	200 – 250	50 und 60	-
960723		7	480 - 500	50 und 60	
		9*	380 – 415	50 und 60	
		12	Supply from an isolating transformer	50 und 60	
		1	Other ratings	Other ratings	
		3	380 440	50 60	
		4	100 – 130	50 und 60	
	4	5	600 - 690	50 und 60	
960724		6*	380 – 415	50 und 60	
		7	480 - 500	50 und 60	IP67 or
			9*	200 – 250	50 und 60
		11	440 - 460	60	
		12	Supply from an isolating transformer	50 und 60	
		1	Other ratings	Other ratings	
		3	220/380 250/440	50 60	
		4	57/100 – 75/130	50 und 60	
	. 5	5	347/600 - 400/690	50 und 60	
960725		6*	200/346 - 240/415	50 und 60	
		7	277/480 - 288/500	50 und 60	
		9*	120/208 - 144/250	50 und 60	
		11	250/440 - 265/460	60	
		12	Supply from an isolating transformer	50 und 60	

* Types with max 2 x socket outlet for household only available for clock position 6h or 9h.