**OVE Austrian Electrotechnical Association** Eschenbachgasse 9 | 1010 Wien | Austria ZVR: 327279890 | www.ove.at

**OVE Certification** Kahlenberger Str. 2A | 1190 Wien | Austria T +43 1 370 58 06 | certification@ove.at

Validity of ÖVE-Certificates can be checked at www.ove.at



Page 1 of 4



including the entitlement to use the Austrian Safety Mark



Certificate No.: 43-250-02

Valid from: 2022 06 06 until: 2024 06 06

The Austrian Electrotechnical Association (OVE) hereby grants the right to the company mentioned below to label the listed products with the Austrian Safety Mark.

Company: PC Electric Ges.m.b.H. Diesseits 145 4973 St. Martin im Innkreis Austria

#### Product: Connector for industrial purposes TopShark 32A

The products submitted by the applicant were type tested in accordance with the requirements of the technical standards and specifications listed in this certificate. OVE certifies the conformity of the listed products and those products manufactured strictly identical to the submitted ones (EN ISO/IEC 17067, Conformity Assessment Scheme Type 5).

The manufacturing process and the products are subject to ongoing surveillance based on harmonized European procedures. This certificate has been issued under the presumption and conditional on the fact that the applicant holds all necessary legal rights with regard to the product, presented for the testing and certification.

Results of testing are shown in file No(s).: TGM-VA EE 37599

Österreichischer Verband für Elektrotechnik Head of OVE Certification

T. NeageEmail=t neumayer@ove.at Digitally signed by T. Neumayer Dipl.-Ing. T. Neumaver

Wien, 2022 04 07

**OVE** Certification







Manufacturer:

PC Electric Ges.m.b.H. Diesseits 145 4973 St. Martin im Innkreis Austria

### Factory location(s):

PC Electric Ges.m.b.H. Diesseits 145 4973 St. Martin im Innkreis Austria

### Tested and certified according to:

ÖVE/ÖNORM EN 60309-1:2013-03-01 ÖVE/ÖNORM EN 60309-2:2013-03-01

This certificate is the basis for the EU Declaration of Conformity and the CE Marking by the manufacturer or his agent and shows the conformity of the certified product(s) with the listed standards as defined by the **EU Low-Voltage Directive 2014/35/EU**. For the presumption of conformity according to Art. 12 with the safety objectives according to Art. 3 of the Directive, transitional periods given in the Official Journal of the European Union have to be observed.

# Product: Connector for industrial purposes TopShark 32A

<b>Type designation:</b> Rating:	Trademark:
2253 Rated current: 32 A 3P+N+PE IP44 or IP44/IP54 Insulation Voltage: 690 V Screw terminals See type code and type list	PCE / ELCEE / SIROX / METECEE
<b>2253TT</b> Rated current: 32 A 3P+N+PE IP44 or IP44/IP54 Insulation Voltage: 690 V screwless terminals See type code and type list	PCE / ELCEE / SIROX / METECEE



Certificate No.: 43-250-02

Date: 2022 04 07

Page 2 of 4

OVE Certification



2	2	5	3	-	6	٦	ГТ	x		v					
												Contact	ts		
												blank	standard contacts		
												v	nickel plated contacts		
												Colour			
								L				blank	identification colour		
												х	special design		
												*	reserved for additional colours		
												Termina	als		
												blank	Screw terminals		
												ТТ	screwless terminals		
												Clock p	osition earthing contact		
					L							1	1 h		
												2	2 h		
												3	3 h		
												4	4 h		
												5	5 h		
												6	6 h		
												7	7 h		
												9	9 h		
												10	10 h		
												11	11 h		
												12	12 h		
												Custom	ner type		
												-	trademark PCE		
												Degree	of protection		
												3	IP44 or IP44/IP54		
												Poles			
												5	5-poles		
												Rated c	urrent		
												2	32A		
												Basic ty	уре		
												2	connector		

## Typecode TOPSHARK Connector 32A

#### **OVE** Certification





Certificate No.: 43-250-02 Date: 2022 04 07 Page 4 of 4

### Typelist

Туре	Poles	 [A]	h	Rated operating voltage [V]	Frequency [Hz]
		6.7	1	Other ratings	Other ratings
			2	>50	>300 -500
			3	220/380	50
			3	250/440	60
		16	4	57/100 - 75/130	50 and 60
2252/TT)	5		5	347/600 - 400/690	50 and 60
2253(TT)	5	10	6	200/346 - 240/415	50 and 60
			7	277/480 - 288/500	50 and 60
			9	120/208 - 144/250	50 and 60
			10	>50	>100-300
			11	250/440 - 265/460	60
			12	Supply from an isolating transformer	50 and 60

